

	EPREL DETAILS	LED75UD18N
1	COMPLIANCE DATA VISIBLE TO UK MSA	
2	ENERGY EFFICIENCY CLASS (SDR MODE)	G
3	ON MODE POWER DEMAND I (SDR) MODE (W)	147.45
4	ENERGY EFFICIENCY CLASS IN HIGH DYNAMIC RANGE (HDR MODE)	G
5	ON MODE POWER DEMAND IN HIGH DYNAMIC RANGE (HDR) MODE (W)	148.85
6	OFF MODE POWER DEMAND (W)	
7	STANDBY MODEL POWER DEMAND (W)	0.25
8	SIZE RATIO (X : Y)	16:09
9	SCREEN RESOLUTION (HORIZONTAL X VERTICAL) (Pixels)	3840*2160
10	PANEL TECHNOLOGY USED	LED Backlight LCD panel
11	AUTOMATIC BRIGHTNESS CONTROL (ABC) AVAILABLE	NO
12	VOICE RECOGNITION SENSOR AVAILABLE	NO
13	ROOM PRESENCE SENSOR AVAILBLE	NO
14	IMAGE REFRESH FREQUENR RATE (HZ)	60
15	POWER SUPPLY TYPE	AC 100-240V
16	MINIMUM GUARANTEED AVAILABILITY OF SOFTWARE AND FIRMWARE UPDATES	
17	MINIMUM GUARANTEED AVAILABILITY OF SPARE PARTS	
18	MINIMUM GUARANTEED PRODUCT SUPPORT	